

Page 1/11

Safety Data Sheet acc. to OSHA HCS

Printing Date 04/23/2020

*

*

Revision Number 3

Revision Date 04/23/2020

Product ide	ntifier
Trade nam	2: <u>FA4844N</u>
Relevant id Adhesive Industrial U	aber: 14158SB entified uses of the substance or mixture. Ise Only. of the substance / the mixture Adhesive
Manufactu Royal Adhe 2001 W. Wa South Bend	he supplier of the safety data sheet rer/Supplier: sives And Sealants, LLC ushington Street IN 46628-2023 Phone Number: 574-246-5000
Emergency ChemTrec:	a department: Global Regulatory Department. telephone number: Day or Night within USA and Canada: 1-800-424-9300. A and Canada: +1 703-527-3887 (collect calls accepted)
) identification on of the substance or mixture
Classificati	on of the substance or mixture HS02 Flame
Classificati	on of the substance or mixture
Classificati	on of the substance or mixture EHS02 Flame 2. H225 Highly flammable liquid and vapor. EHS08 Health hazard H361 Suspected of damaging fertility or the unborn child.
Classificati Flam. Liq. 2 Flam. Liq. 2 Repr. 2 STOT RE 2	on of the substance or mixture GHS02 Flame 2. H225 Highly flammable liquid and vapor. GHS08 Health hazard
Classificati	on of the substance or mixture GHS02 Flame 2: H225 Highly flammable liquid and vapor. GHS08 Health hazard H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.
Classificati Flam. Liq. 2 Flam. Liq. 2 C Repr. 2 STOT RE 2 Asp. Tox. 1 C	on of the substance or mixture HS02 Flame 2 H225 Highly flammable liquid and vapor. HS08 Health hazard H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.
Classificati Flam. Liq. 2 Flam. Liq. 2 Flam. Liq. 2 C Repr. 2 STOT RE 2 Asp. Tox. 1	on of the substance or mixture EHS02 Flame 2: H225 Highly flammable liquid and vapor. EHS08 Health hazard H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways.

Printing Date 04/23/2020

Revision Number 3

Revision Date 04/23/2020

Trade name: FA4844N

(Contd. of page 1)

Hazard pictograms	(Contd. of page
GHS02 GHS07 GHS08	
Signal word Danger	
Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower	r.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>15</i> .
Classification system:	
NFPA ratings (scale 0 - 4)	
$\begin{array}{c} \textbf{Health} = 2\\ Fire = 3 \end{array}$	
2 0 Fire = 5 Reactivity = 0	
\sim Keachvaly = 0	
HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 $Fire = 3$	
PHYSICAL HAZARD Physical Hazard = 0	

(Contd. on page 3)

Revision Date 04/23/2020

Trade name: FA4844N

· Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture

· Hazardous components:			
108-88-3	toluene	25-50%	
110-54-3	n-hexane	5-20%	
68410-97-9	Distillates (petroleum), light distillate hydrotreating process, low-boiling	2.5-10%	
110-82-7	cyclohexane	2.5-10%	

4 First-aid measures

· Description of first aid measures

- After inhalation:
- Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Wipe excess from skin. Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

• After swallowing:

Rinse mouth with water.

Do not induce vomiting. Obtain medical advice.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available. • Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

• *Protective equipment: Protective clothing and respiratory protective device.*

(Contd. on page 4)

US/

Printing Date 04/23/2020

Revision Number 3

(Contd. of page 2)

Printing Date 04/23/2020

Revision Number 3

Revision Date 04/23/2020

Trade name: FA4844N

(Contd. of page 3)

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Open and handle receptacle with care. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep container closed when not in use. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- *Specific end use*(*s*) *No further relevant information available.*

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

108-88-3 toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift REL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm BEI

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Revision Date 04/23/2020

Printing Date 04/23/2020 Trade name: FA4844N

110-54-3 n-hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

Revision Number 3

REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 176 mg/m³, 50 ppm
	Skin; BEI
110-8	82-7 cyclohexane
PEL	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 344 mg/m³, 100 ppm
-	edients with biological limit values:
108-8	88-3 toluene
	0.02 mg/L
	Medium: blood
	Time: prior to last shift of workweek
	Parameter: Toluene
	0.03 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Toluene
	0.3 mg/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: o-Cresol with hydrolysis (background)
110-:	54-3 n-hexane
BEI	0.4 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: 2.5-Hexanedione without hydrolysis
· Addi	tional information: The lists that were valid during the creation were used as basis.
· Expo	sure controls
-	onal protective equipment (see listings below)
	ral protective and hygienic measures:
Keep	away from foodstuffs, beverages and feed.
Imme	ediately remove all soiled and contaminated clothing

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

 ${\it Store\ protective\ clothing\ separately}.$

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Revision Number 3

Revision Date 04/23/2020

Printing Date 04/23/2020

Trade name: FA4844N

(Contd. of page 5)

• *Material of gloves Nitrile rubber, NBR*

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

• *Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

• Eye protection:

Safety glasses with side shields.

Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

 Information on basic physical and c General Information 	nemicai properties
· Appearance:	
Form:	Liquid
Color:	Not determined.
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point:	Undetermined.
Boiling point:	69 °C (156.2 °F)
· Flash point:	-26 °C (-14.8 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Flammable limits:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
· Specific gravity at 20 °C (68 °F):	0.859 g/cm ³ (7.16836 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.

USA –

Printing Date 04/23/2020

Revision Number 3

Revision Date 04/23/2020

Trade name: FA4844N

		(Contd. of page 6
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octan		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	Not available	
Solids content:	Not available.	
• Other information	Pounds Per Gallon 7.17	
-	Lbs VOC/Gallon [less water. less exempts] 5.50	
	Grams VOC/Liter [less water. less exempts] 658.68	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions not reactive, as supplied.
- · Conditions to avoid Heat, flames, sparks.
- *Incompatible materials: Reacts with oxidizing agents. Reacts with acids.*
- Hazardous decomposition products: Carbon monoxide and carbon dioxide Hydrogen chloride (HCl) Hydrocarbons

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

100-00-31	oluene	
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

Oral LD50 12,705 mg/kg (rat)

- · Primary irritant effect:
- on the skin: Skin irritant.
- \cdot on the eye:
- May irritate the eye.
- Vapors may be irritating to the eyes.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)

Revision Number 3

Revision Date 04/23/2020

Printing Date 04/23/2020

Trade name: FA4844N

(Contd. of page 7)

3

Irritant The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-88-3 toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Comply with current regulations.

· Uncleaned packagings:

· Recommendation: Comply with current regulations.

· UN-Number		
· DOT, IMDG, IATA	UN1133	
· UN proper shipping name		
$\cdot DOT$	Adhesives	
· IMDG, IATA	ADHESIVES	

USA

Revision Number 3

Revision Date 04/23/2020

Printing Date 04/23/2020
Trade name: FA4844N

	(Contd. of pag
Transport hazard class(es)	
DOT	
R AMMARIE FLOUD	
3	
Class	2 Elammable liquide
Label	3 Flammable liquids 3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	11
Environmental hazards:	Product contains environmentally hazardous substances:
	cyclohexane
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler): EMS Number:	33 E E S D
EMS Number: Stowage Category	F-E,S-D B
Transport in bulk according to Annex . MARPOL73/78 and the IBC Code	<i>II of</i> Not applicable.
Transport/Additional information:	
DOT	This product is not regulated as a marine pollutant when
	transported on inland waterways in sizes of $\leq 5 L$ or $\leq 5 kg$ or by
	road, rail, or inland air in nonbulk sizes, provided the packaging meets the general requirements 173.24 and 173.24a.
IMDC	
IMDG	The marine pollutant mark is not required when transported in size of $\leq 5 L$ or $\leq 5 \text{ kg}$.
IATA	The environmentally hazardous substance mark may appear if required by other transport regulations.
UN ''Model Regulation'':	UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)

USA

Revision Number 3

Revision Date 04/23/2020

Printing Date 04/23/2020

Trade name: FA4844N

(Contd. of page 9)

• Section 313 (Specific toxic	c chemical listings):
-------------------------------	-----------------------

108-88-3 toluene

110-54-3 n-hexane 110-82-7 cyclohexane

110 02 / Cyclonexane

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Hazardous Air Pollutants

108-88-3 toluene

110-54-3 n-hexane

· Proposition 65

Please contact H.B. Fuller for more information regarding Proposition 65 on this product:

reg.request@hbfuller.com.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)108-88-3toluene110-54-3n-hexane110-82-7cyclohexane110-82-7cyclohexane· TLV (Threshold Limit Value established by ACGIH)108-88-3toluene108-88

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. *Exceptions can be made by the authorities in certain cases.*

• Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

• Department issuing SDS:

Global Regulatory Department. reg.request@hbfuller.com • Creation Date: 04/23/2020

(Contd. on page 11)

USA

Printing Date 04/23/2020

Revision Number 3

Revision Date 04/23/2020

Trade name: FA4844N

	(Contd. of page 10)
• Date of preparation / last revision 04/23/2020 / 2	
· Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the	International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
	USA -

USA