

SDS Revision: Version 1.3  
SDS Revision Date: 12/27/2018

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity** UK 148 Mixed  
**Alternate Names** UK 148 2 part kit mixed together  
(See separate SDS for each kit component)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** See Technical Data Sheet.  
**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** STABOND CORPORATION  
1722 W. 139th Street, GARDENA CA. 90249  
**Customer Service: STABOND CORPORATION** (310) 380-6168 Mon. to Fri. 07:00 – 15:30 PT  
**Emergency Contact: CHEMTREC** (800) 424-9300 24-hour

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Resp. Sens. 1;H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2;H351	Suspected of causing cancer.
Repr. 2;H361D	Suspected of damaging the unborn child.
STOT SE 3;H336	May cause drowsiness or dizziness.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness and dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

**[Prevention]:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

**[Response]:**

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P342+311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor / physician.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

**[Storage]:**

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

**[Disposal]:**

P501 Dispose of contents / container in accordance with local / national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Butanone CAS Number: 0000078-93-3	50 - 75	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene] CAS Number: 0030662-91-0	10 - 25		[1]
n-Propyl Acetate CAS Number: 0000109-60-4	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Toluene CAS Number: 0000108-88-3	1.0 - 10	Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]
Diphenylmethanediisocyanate CAS Number: 0000101-68-8	1.0 - 10	Carc. 2;H351 Acute tox. 4;H332 STOT RE 2;H373 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317	[1][2]
Ethanol, 2-butoxy-, phosphate (3:1) CAS Number: 0000078-51-3	1.0 - 10		[1]
Polymeric Diphenylmethane Diisocyanate CAS Number: 0009016-87-9	1.0 - 10	Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Sens. 1;H317 Resp. Sens. 1;H334	[1]
Diphenylmethane diisocyanate, mixed isomers CAS Number: 0026447-40-5	0.10 - 1.0	Carc. 2;H351 Acute tox. 4;H332 STOT RE 2;H373 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Resp. Sens. 1;H334 Skin Sens. 1;H317	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. If vomiting should occur spontaneously keep victims head below knees to prevent aspiration into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Overview</b>	<p>This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.</p> <p>Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.</p> <p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
<b>Inhalation</b>	May cause drowsiness or dizziness. May cause allergy or asthma symptoms of breathing difficulties if inhaled.
<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	May cause an allergic skin reaction. Causes skin irritation.
<b>Chronic effects</b>	Moderate CNS depression may be shown by giddiness, headache, dizziness and nausea. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs, which can cause severe lung damage. Aspiration pneumonitis may be evidenced by coughing and cyanosis.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use; water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce fumes of carbon dioxide, carbon monoxide, hydrogen cyanide, phenols and nitrous oxides

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Avoid breathing dust / fume / gas / mist / vapors / spray.

### 5.3. Advice for fire-fighters

Volatile solvent constituent can readily form explosive or flammable mixtures in air. Vapors can flow along surfaces to distant ignition sources and flash back.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. 127

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, Do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapor levels are below the Lower Explosive Limit before re-entering.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Soak up wet material on a non-combustible absorbent and place in a closed metal container.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Store in cool, well ventilated area away from any ignition sources and strong oxidizing agents. Keep containers tightly closed when not in use. Do not transfer to plastic containers.

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Precautions should be taken to minimize exposure to atmospheric humidity or water as carbon dioxide may be formed which, in closed containers can result in pressurization. Care should be taken when re-opening partly used containers.

Ground and bond metal containers when dispensing. Not smoking in areas of use or storage. Use only non-sparking tools near wet adhesive or solvent vapors. Solvent vapor is much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons applying this preparation.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

Exposure			
CAS No.	Ingredient	Source	Value
0000078-51-3	Ethanol, 2-butoxy-, phosphate (3:1)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000078-93-3	Butanone	OSHA	TWA 200 ppm (590 mg/m3)
		ACGIH	TWA: 50 ppm STEL: 100 ppm
		NIOSH	TWA 200 ppm (590 mg/m3) ST 300 ppm (885 mg/m3)
		Supplier	No Established Limit
0000101-68-8	Diphenylmethanediisocyanate	OSHA	C 0.2 mg/m3 (0.02 ppm)
		ACGIH	TWA: 0.005 ppm Ceiling: 0.01 ppm Skin, S
		NIOSH	TWA 0.05 mg/m3 (0.005 ppm) C 0.2 mg/m3 (0.020 ppm) [10-minute]
		Supplier	No Established Limit
0000108-88-3	Toluene	OSHA	TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak) STEL 150 ppm
		ACGIH	TWA: 20 ppmR
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit
0000109-60-4	n-Propyl Acetate	OSHA	TWA 200 ppm (840 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm
		NIOSH	TWA 200 ppm (840 mg/m3) ST 250 ppm (1050 mg/m3)
		Supplier	No Established Limit
0009016-87-9	Polymeric Diphenylmethane Diisocyanate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0026447-40-5	Diphenylmethane diisocyanate, mixed isomers	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0030662-91-0	Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene]	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000078-51-3	Ethanol, 2-butoxy-, phosphate (3:1)	OSHA	Select Carcinogen: No

		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000078-93-3	Butanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000101-68-8	Diphenylmethanediisocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000109-60-4	n-Propyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009016-87-9	Polymeric Diphenylmethane Diisocyanate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0026447-40-5	Diphenylmethane diisocyanate, mixed isomers	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0030662-91-0	Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene]	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

## 8.2. Exposure controls

### Respiratory

Atmospheric levels should be maintained below the exposure guideline. Use an approved, full-face, supplied air respirator or a NIOSH approved positive pressure, self-contained breathing apparatus if these levels are exceeded.

### Eyes

Safety glasses or chemical goggles should be worn.

### Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Use neoprene, vinyl or natural rubber gloves.

### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

### Other Work Practices

Eye wash fountain or bottles. Solvent insoluble barrier hand cream. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

**Appearance**

MEDIUM VISCOSITY CLEAR Liquid

**Odor**

Not Measured

**Odor threshold**

Not Measured

pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	175 F TO 231 F
Flash Point	16 F TCC
Evaporation rate (Ether = 1)	SLOWER THAN ETHER
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	<b>Lower Explosive Limit:</b> 1.0 % <b>Upper Explosive Limit:</b> 11.4%
Vapor pressure (Pa)	Not Measured
Vapor Density	HEAVIER THAN AIR
Specific Gravity	0.9 (H2O=1)
Solubility in Water	Nil
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	COATING V.O.C.: 5.68 LB/GAL (681 G/L), MATERIAL V.O.C.: 5.68 LB/GAL (681 G/L)

## 9.2. Other information

No other relevant information.

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Excessive heat and open flame.

### 10.5. Incompatible materials

Strong oxidizing agents and acids can cause spontaneous combustion.

### 10.6. Hazardous decomposition products

Burning may produce fumes of carbon dioxide, carbon monoxide, hydrogen cyanide, phenols and nitrous oxides.

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.



Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

Based on the properties of the isocyanate content of this product, respiratory exposure may cause acute irritation and/or sensitisation of the respiratory system resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Butanone - (78-93-3)	2,737.00, Rat - Category: 5	6,480.00, Rabbit - Category: NA	32.00, Mouse - Category: NA	No data available	No data available
Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene] - (30662-91-0)	No data available	No data available	No data available	No data available	No data available
n-Propyl Acetate - (109-60-4)	9,370.00, Rat - Category: NA	17,740.00, Rabbit - Category: NA	No data available	No data available	No data available
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available
Diphenylmethanediisocyanate - (101-68-8)	4,700.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Ethanol, 2-butoxy-, phosphate (3:1) - (78-51-3)	No data available	No data available	No data available	No data available	No data available
Polymeric Diphenylmethane Diisocyanate - (9016-87-9)	49,000.00, Rat - Category: NA	9,400.00, Rabbit - Category: NA	No data available	No data available	No data available
Diphenylmethane diisocyanate, mixed isomers - (26447-40-5)	6,400.00, Rat - Category: NA	6,200.00, Rabbit - Category: NA	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	1	May cause allergy or asthma symptoms of breathing difficulties if inhaled.
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.

Reproductive toxicity	2	Suspected of damaging the unborn child.
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Butanone - (78-93-3)	400.00, Cyprinodon variegatus	520.00, Daphnia magna	500.00 (96 hr), Skeletonema costatum
Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene] - (30662-91-0)	Not Available	Not Available	Not Available
n-Propyl Acetate - (109-60-4)	60.00, Pimephales promelas	318.00, Daphnia magna	1,000.00 (72 hr), Chlorococcales
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available
Diphenylmethanediisocyanate - (101-68-8)	Not Available	129.70, Daphnia magna	Not Available
Ethanol, 2-butoxy-, phosphate (3:1) - (78-51-3)	Not Available	Not Available	Not Available
Polymeric Diphenylmethane Diisocyanate - (9016-87-9)	Not Available	Not Available	Not Available
Diphenylmethane diisocyanate, mixed isomers - (26447-40-5)	Not Available	1,000.00, Daphnia magna	4,300.00 (72 hr), Chlorella vulgaris

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
<b>14.1. UN number</b>	UN1133	UN1133	UN1133
<b>14.2. UN proper shipping name</b>	UN1133, Adhesives, containing a flammable liquid, 3, II	Adhesives, containing a flammable liquid	Adhesives, containing a flammable liquid
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> 3 <b>DOT Label:</b> 3	<b>IMDG:</b> 3 <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> 3
<b>14.4. Packing group</b>	II	II	II
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>	No further information		

## 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	B2 D2A
<b>US EPA Tier II Hazards</b>	<p style="text-align: right;"><b>Fire:</b> Yes</p> <p style="text-align: right;"><b>Sudden Release of Pressure:</b> No</p> <p style="text-align: right;"><b>Reactive:</b> No</p> <p style="text-align: right;"><b>Immediate (Acute):</b> Yes</p> <p style="text-align: right;"><b>Delayed (Chronic):</b> Yes</p>

### EPCRA 311/312 Chemicals and RQs (lbs):

Butanone	( 5,000.00)
Diphenylmethanediisocyanate	( 5,000.00)
Toluene	( 1,000.00)

**EPCRA 302 Extremely Hazardous :** (No Product Ingredients Listed)

### EPCRA 313 Toxic Chemicals:

Diphenylmethanediisocyanate
Polymeric Diphenylmethane Diisocyanate
Toluene

**Proposition 65 - Carcinogens (>0.0%):** (No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0.0%):**

Toluene

**Proposition 65 - Female Repro Toxins (>0.0%):** (No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):** (No Product Ingredients Listed)

**N.J. RTK Substances (>1%):**

Butanone  
Diphenylmethanediisocyanate  
n-Propyl Acetate  
Polymeric Diphenylmethane Diisocyanate  
Toluene

**Penn RTK Substances (>1%):**

Butanone  
Diphenylmethanediisocyanate  
n-Propyl Acetate  
Toluene

**16. Other information**

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergic or asthmatic symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

**SDS Revision History**

<b>Version 1.1</b>	<b>Initial SDS issued</b>	<b>11/20/2014</b>
<b>Version 1.2</b>	<b>Section 1.3 Change to Emergency Tele. Number</b>	<b>6/17/2015</b>
<b>Version 1.3</b>	<b>Section 1.3 Update to Emergency Tele. Number</b>	<b>12/27/2018</b>

ALL INFORMATION IS BASED UPON DATA FROM MFG'S AND/OR TECHNICAL SOURCE, & IS BELIEVED TO BE ACCURATE. CONDITIONS OF USE ARE BEYOND OUR CONTROL & THEREFORE USERS ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN CONDITIONS TO DETERMINE SUITABILITY FOR THEIR PURPOSE, & THEY ASSUME ALL RISKS OF USE, HANDLING, & DISPOSAL, OR FROM USE OF INFORMATION CONTAINED HEREIN. THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH OTHER MATERIAL OR IN ANY OTHER PROCESS.

End of Document